



SynBlend/High Mileage 20W50

(API SN, ACEA A3/B4)

Our PCMO SynBlend/High Mileage SAE 20W50 is designed for use in modern fuel injected gasoline engines, formulated with synthetic and high-viscosity index Type II paraffinic base oils and a special additive package designed for superior protection against wear, corrosion, oxidation and varnish.

- Furthermore, a unique detergent additive prevents sludge or carbon deposits especially in extreme heat or pressure conditions. API License #3355.
- It enhances engine performance, extends oil life, ease cold-starts and eliminates viscosity breakdown.
- Specially formulated to be used in Cars, Vans, Light Trucks and Trucks with over 75,000 Miles or (120,000Kms).
- The API SN category was Introduced in October 2010, designed to provide improved high temperature deposit protection for pistons, more stringent sludge control, and seal compatibility.
- Meets European Specification ACEA A3/B4.
- Available in Bulk, 275Gall, 55Gall, 5Gall, 4/5Qts, 12/1Qts



Typical Inspections

Color
Specific Gravity @ 15.6°C
Viscosity Index
Pour Point °C (°F)
Flash Point C.O.C. °C (°F)
Viscosity @ 40°C, cSt
Viscosity @ 100°C, cSt

Method

Visual
ASTM D-1298
ASTM D-2270
ASTM D-97
ASTM D-92
ASTM D-445
ASTM D-445

Typical Results

Brilliant, Amber
.889
127
-38 (-36.4)
230 (446)
179
19.8

Meets/Exceeds Specifications

API SN
ACEA A3/B4
SAE 20W50

Meets/Exceeds OEM Requirements

CHRYSLER MS-6395
FORD WSS-M2C945-A
GM-6094M
HONDA
MERCEDES BENZ 229.3
TOYOTA
VW 501.01 & 505.00

Note: The general description, recommended uses, application data and statements in the product literature are guidelines. Because the product may be used for a variety of applications, over which **Carteroil USA Inc.** has no control. **Carteroil USA Inc.** assumes no liability for incidentals, consequential, or direct damage of any kind, regardless of causes, including negligence. For more information please visit us at www.carteroilusa.com

