

PCMO/Conventional SAE 10W30 (APISN, ILSAC GF-5)

Our PCMO Conventional Motor Oil SAE 5W20, API SN is designed for use in modern fuel injected gasoline engines, formulated with high-viscosity index Type II paraffinic base oils and a special additive package designed for superior protection against wear, corrosion, oxidation and varnish.

- Furthermore, a unique detergent additive prevents sludge or carbon deposits especially in extreme heat or pressure conditions.
- · With approved API License #3355.
- · It enhances engine performance, extend oil life, ease cold-starts, and eliminate viscosity breakdown.
- · Specially formulated to be used in Cars, Vans, Light Trucks and Trucks.
- The API SN category was Introduced in October 2010, designed to provide improved high temperature deposit protection for pistons, more stringent sludge control, and seal compatibility.
- API SN with Resource Conserving matches ILSAC GF-5 by combining API SN performance with improved fuel economy, turbocharger protection, emission control system compatibility, and protection of engines operating on ethanol-containing fuels up to E85.
- · Available in Bulk, 275Gall, 55Gall, 5Gall, 12/1Qts.

Typical Inspections	Method	Typical Results
Color	Visual	Brillant, Amber
Specific Gravity @ 15.6°C	ASTM D-1298	.887
Viscosity Index	ASTM D-2270	123
Pour Point °C (°F)	ASTM D-97	-38 (-36.4)
Flash Point C.O.C. °C (°F)	ASTM D-92	211 (412)
Viscosity @ 40°C, cSt	ASTM D-445	81.4
Viscosity @ 100°C, cSt	ASTM D-445	10.8

Meets/Exceeds Specifications

API SN SAE 10W30 II SAC GF-5

Meets/Exceeds OEM Requirements

CHRYSLER MS-6395
FORD WSS-M2C945-A
GM-6094M
HONDA
MERCEDES BENZ 229.3
TOYOTA



