



# PCMO/Conventional SAE 15W40 (API SN)

- Our PCMO Conventional Motor Oil SAE 15W40, API SN is designed for use in modern fuel injected gasoline engines, formulated with high-viscosity index Type II paraffinic base oils and a special additive package designed for superior protection against wear, corrosion, oxidation and varnish.
- Furthermore, a unique detergent additive prevents sludge or carbon deposits especially in extreme heat or pressure conditions.
- It enhances engine performance, extend oil life, ease cold-starts, and eliminate viscosity breakdown.
- Specially formulated to be used in Cars, Vans, Light Trucks and Trucks.
- The API SN category was Introduced in October 2010, designed to provide improved high temperature deposit protection for pistons, more stringent sludge control, and seal compatibility.
- Available in Bulk, 275Gall, 55Gall, 5Gall, 12/1Qts.



## Typical Inspections

Color  
 Specific Gravity @ 15.6°C  
 Viscosity Index  
 Pour Point °C (°F)  
 Flash Point C.O.C. °C (°F)  
 Viscosity @ 40°C, cSt  
 Viscosity @ 100°C, cSt

## Method

Visual  
 ASTM D-1298  
 ASTM D-2270  
 ASTM D-97  
 ASTM D-92  
 ASTM D-445  
 ASTM D-445

## Typical Results

Brilliant, Amber  
 .889  
 127  
 -38 (-36.4)  
 228 (442.4)  
 108  
 14.2

## Meets/Exceeds Specifications

API SN  
 SAE 10W40

## Meets/Exceeds OEM Requirements

CHRYSLER MS-6395  
 FORD WSS-M2C945-A  
 GM-6094M  
 HONDA  
 MERCEDES BENZ 229.3  
 TOYOTA

Note: The general description, recommended uses, application data and statements in the product literature are guidelines. Because the product may be used for a variety of applications, over which **Carteroil USA Inc.** has no control, **Carteroil USA Inc.** assumes no liability for incidentals, consequential, or direct damage of any kind, regardless of causes, including negligence. For more information please visit us at [www.carteroilusa.com](http://www.carteroilusa.com)

