

## PCMO/Conventional SAE 20W50 (API SN,ACEA A3/B4)

- Our PCMO Conventional Motor Oil SAE 20W50, API SN is designed for use in modern fuel injected gasoline engines, formulated with high-viscosity index Type II paraffinic base oils and a special additive package designed for superior protection against wear, corrosion, oxidation and varnish.
- Furthermore, a unique detergent additive prevents sludge or carbon deposits especially in extreme heat or pressure conditions.
- · With approved API License #3355.
- · It enhances engine performance, extend oil life, ease cold-starts, and eliminate viscosity breakdown.
- · Specially formulated to be used in Cars, Vans, Light Trucks and Trucks.
- The API SN category was Introduced in October 2010, designed to provide improved high temperature deposit protection for pistons, more stringent sludge control, and seal compatibility.
- Meets European Specification ACEA A3/B4.
- · Available in Bulk, 275Gall, 55Gall, 5Gall, 12/1Qts

Typical Inspections	Method	Typical Results
Color	Visual	Brillant, Amber
Specific Gravity @ 15.6°C	ASTM D-1298	.889
Viscosity Index	ASTM D-2270	127
Pour Point °C (°F)	ASTM D-97	-38 (-36.4)
Flash Point C.O.C. °C (°F)	ASTM D-92	230 (446)
Viscosity @ 40°C, cSt	ASTM D-445	179
Viscosity @ 100°C, cSt	ASTM D-445	19.8

## **Meets/Exceeds Specifications**

API SN SAE20W50 ACEA A3/B4

## **Meets/Exceeds OEM Requirements**

CHRYSLER MS-6395 FORD WSS-M2C945-A GM-6094M HONDA MERCEDES BENZ 229.3

TOYOTA

VW 501.01 & 505.00



ORIGINAL