



CARTEROIL

18-Wheeler Trucks LUBRICATION GUIDE

ENGINE MOTOR OIL

- Full Synthetic SAE 15W40 (API CK-4/SN.TBN 9)
- SynBlend SAE 15W40 (API CK-4/SN. TBN9)
- SynBlend SAE 15W40 (API CJ-4/SN. TBN8)
- SynBlend SAE 20W50 (API CJ-4/SN. TBN8)
- HDMO SAE 15W40 (API CI-4/SL, CI4 Plus TBN10)
- HDMO SAE 50 (API CF/SL, TBN8)

UNIVERSAL JOINTS

- Lithium Molly EP No.2 (Grey)

5th WHEEL/CHASSIS

- MPL Multipurpose No. 2 (Amber)

WHEEL BEARINGS

- HT High Temperature No.2 (RED)

DIFFERENTIAL/GEAR

- Full Synthetic SAE 80W140 (API GL-5/MT-1)
- Gear Oil SAE 85W140 (API GL-5/MT-1)
- Gear Oil SAE 140 (API GL-5)
- Gear Oil SAE 140 (API GL-1)

TRANSMISSIONS (Manual/Automatic)

- Full Synthetic SAE 75W90 (API GL-5/MT-1)
- Full Synthetic Manual Transmission SAE 50 (API MT-1, D-50)
- Gear Oil SAE 80W90 (API GL-5/MT-1)
- Gear Oil SAE 90 (API GL-5)
- Gear Oil SAE 90 (API GL-1)

HYDRAULIC STEERING

- ATF Dexron-III/MERCON

ANTIFREEZE - COOLANT

- Antifreeze/Coolant, Concentrate (Red)
- Antifreeze/Coolant, 50% - 50% (Red)



Private Labeling Available

* Consult the engine manufacturer for service interval recommendations.

** The general description, recommended uses, application data and statements are guidelines. Because the product may be used for a variety of applications, over which Carteroil USA Inc. has no control. Carteroil USA Inc. assumes no liability for incidentals, consequential, or direct damage of any kind, regardless of causes, including negligence. For more information please visit us at: www.carteroilusa.com