



CARTEROIL

H-Duty Tow Trucks LUBRICATION GUIDE



HYDRAULIC SYSTEM

- Hydraulic Oil ISO 68 (AW, R&O, 5000 Hrs.)



ENGINE MOTOR OIL

- Full Synthetic SAE 5W30 (API CK-4/SN.TBN 9)
- Full Synthetic SAE 5W40 (API CK-4/SN.TBN 9)
- SynBlend SAE 10W30 (API CK-4/SN. TBN9)
- SynBlend SAE 15W40 (API CJ-4/SN. TBN8)
- SynBlend SAE 20W50 (API CJ-4/SN. TBN8)
- HDMO SAE 15W40 (API CI-4/SL, CI4 Plus TBN10)



ANTIFREEZE - COOLANT

- Antifreeze/Coolant, Concentrate (Red)
- Antifreeze/Coolant, 50% - 50% (Red)



WHEEL BEARINGS

- HT High Temperature No.2 (RED)



DIFFERENTIAL/GEAR

- Full Synthetic SAE 75W90 (API GL-5/MT-1)
- Gear Oil SAE 80W90 (API GL-5/MT-1)



TRANSMISSIONS (Manual/Automatic)

- Full Synthetic MT SAE 50 (API MT-1, CD-50)
- ATF - Global Full Synthetic



GREASE POINTS

RODS, PINS, CLUTCH BEARINGS

- Lithium EP No. 2 (Amber)
- HT High Temperature No. 2 (RED)



Private Labeling Available

* Consult the engine manufacturer for service interval recommendations.

** The general description, recommended uses, application data and statements are guidelines. Because the product may be used for a variety of applications, over which Carteroil USA Inc. has no control. Carteroil USA Inc. assumes no liability for incidentals, consequential, or direct damage of any kind, regardless of causes, including negligence. For more information please visit us at: www.carteroilusa.com