



CARTEROIL

Light Duty Diesel Trucks LUBRICATION GUIDE

ANTIFREEZE - COOLANT

- Antifreeze/Coolant, Concentrate (Red)
- Antifreeze/Coolant, 50% - 50% (Red)

ENGINE MOTOR OIL

- Full Synthetic SAE 5W30 (API CK-4/SN.TBN 9)
- Full Synthetic SAE 5W40 (API CK-4/SN. TBN9)
- SynBlend SAE 15W40 (API CK-4/SN. TBN9)
- SynBlend SAE 10W30 (API CK-4/SN. TBN9)
- SynBlend SAE 15W40 (API Cj-4/SN. TBN8)



Private Labeling Available

POWER STEERING

- PSF (Power Steering Fluid)

TRANSMISSIONS (Automatic)

- ATF-Full Synthetic Global
- DEX VI-Full Synthetic
- ATF-Dexron-III/MERCON

GREASE POINTS, RODS, PINS/BEARINGS

- HT High Temperature No.2 (RED)
- Lithium EP No. 2 (Amber)

DIFFERENTIAL/GEAR

- Full Synthetic SAE 75W90 (API GL-5/MT-1)
- Gear Oil SAE 80W90 (API GL-5/MT-1)



* Consult the engine manufacturer for service interval recommendations.

** The general description, recommended uses, application data and statements are guidelines. Because the product may be used for a variety of applications, over which Carteroil USA Inc. has no control. Carteroil USA Inc. assumes no liability for incidentals, consequential, or direct damage of any kind, regardless of causes, including negligence. For more information please visit us at: www.carteroilusa.com