



CARTEROIL

Wheel Loaders LUBRICATION GUIDE

HYDRAULIC SYSTEM

- Hydraulic Oil ISO 68 (AW, R&O, 5000Hrs)
- Drive Train Fluid SAE 10W (TO-4)

ENGINE MOTOR OIL

- Full Synthetic SAE 5W40 (API CK-4/SN.TBN 9)
- SynBlend SAE 15W40 (API CJ-4/SN. TBN9)
- SynBlend SAE 15W40 (API CJ-4/SN. TBN8)
- HDMO SAE 15W40 (API CI-4/SL, CI4 Plus TBN10)

WHEEL BEARINGS GREASE POINTS

- HT High Temperature No. 2 (RED)
- Lithium Molly EP No.2 (Dark Grey)

ANTIFREEZE - COOLANT

- Antifreeze/Coolant, Concentrate (Red)
- Antifreeze/Coolant, 50% - 50% (Red)

TRANSMISSION

- Drive Train Fluid SAE 10W (TO-4)
- ULTRA Transmission Drive Train Oil (TO-4M)

GEAR DRIVE

- Drive Train Fluid SAE 50 (TO-4)
- Drive Train Fluid SAE 60 (TO-4)



Private Labeling Available

* Consult the engine manufacturer for service interval recommendations.

** The general description, recommended uses, application data and statements are guidelines. Because the product may be used for a variety of applications, over which Carteroil USA Inc. has no control. Carteroil USA Inc. assumes no liability for incidentals, consequential, or direct damage of any kind, regardless of causes, including negligence. For more information please visit us at: www.carteroilusa.com